

Manila rope blocks

(made of stainless steel)



No. 91



No. 92



No. 95

No. 91 - 95 Manila rope blocks (rope pulleys) made of stainless steel

AISI 304 stainless steel, with swivel oval eye and rope eye. The blocks are equipped with stainless steel sheaves with brass bushing. All dimensions in mm.

Sheave external Ø		75	100	125
Groove base Ø		60	80	103
for rope Ø up to		14	16	18
Casing width		84	112	145
No. 91	Oval eye, perm. load kg	500	750	1000
with	Oval eye, internal dim.	24 x 38	24 x 38	32 x 41
1 sheave	Axle length	49	52	60
	Total length incl. oval eye	250	310	360
	Weight in kg approx.	1.00	1.85	2.45
No. 92	Oval eye, perm. load kg	750	1000	1250
with	Oval eye, internal dim.	24 x 38	24 x 38	32 x 41
2 sheaves	Axle length	78	80	85
	Total length incl. oval eye	250	310	360
	Weight in kg approx.	1.52	2.80	3.60
No. 95	Oval eye, perm. load kg	500	750	1000
with	Oval eye, internal dim.	24 x 38	24 x 38	32 x 41
1 sheave	Axle length	49	52	60
hinged	Total length incl. oval eye	250	310	360
	Weight in kg approx.	1.10	1.95	2.55

Replacement sheaves for stainless steel manila rope blocks

No. 91 - 95

No. 96 Stainless steel sheaves with brass bushing

made of grade 1.4104 stainless steel. All dimensions in mm.



Sheave external Ø	25	32	50	75	100	125
Groove base Ø	17	21	34	60	80	103
Groove radius	6	6	7.5	7	9	10
Groove depth	5	5	8	7	10	10
Rim width	17	17	21	20	25	25
Bore for bolt	8	8	10	13	17	17
Hub length	17	17	21	21	26	28
Hub Ø	-	-	23	30	35	35
Rope Ø max.	10	10	14	14	16	18
Load capacity in kg	150	150	250	500	750	1000
Weight in kg approx.	0.04	0.06	0.16	0.28	0.56	0.59